



- Hot water storage tank exclusively stainless steel, material 1.4571/ 1.4404 pickled and neutralized.
- All Rp-connections are inside thread according to EN 10226.
- The 100 mm-thick flexible ULIES insulation ensures economical operation by minimizing heat loss. (The insulation casing of the tanks can easily be unmounted and re-mounted. They are made with cleanable casing, polystyrene cover, in silver colour and specifically to fit the parameters of the tanks.)
- Reserves the right to make technical changes without notice!

Measurements from 200 to 3000 liter

dimensions in mm

capacity (l)	200	300	500	750	1000	1250	1500	2000	3000
H1	65	65	65	80	80	80	80	80	70
H2	455	455	505	550	680	580	645	709	1000
H3	1000	1225	1520	1565	1380	1480	1615	1579	2040
H4*	-	-	-	-	-	-	-	1759	-
H5	1430	1700	1974	2059	1867	2367	2147	2485	2779
H	1442	1712	1986	2071	1879	2389	2160	2498	2793
D1 diameter	500	500	600	750	900	900	1000	1100	1300
D2 insulated diameter	700	700	800	950	1100	1100	1200	1300	1500
weight (kg)	35	40	53	92	116	144	158	232	364

connections

capacity (l)	200	300	500	750	1000	1250	1500	2000	3000
H2, H4*	120/180	120/180	120/180	120/180	120/180	120/180	120/180	120/180	400/480
H1, H5	Rp 1 ¼"	Rp 1 ¼"	Rp 1 ¼"	Rp 1 ¼"	Rp 1 ¼"	Rp 1 ½"	Rp 2"	Rp 2"	Rp 2 ½"
H3	Rp 1/2"	Rp 1/2"	Rp 1/2"	Rp 1/2"	Rp 1/2"	Rp 1/2"	Rp 1/2"	Rp 1/2"	Rp 1/2"

* The 2000 liter tank has two inspection flanges (120/180mm).